



MULTI-FREQUENCY, MULTI-GNSS ANTENNA



The RX45 GNSS antenna is designed to support millimeter-level accuracy on land and marine applications. The RX45 GNSS antenna offers support for present and future GNSS signals, including GPS, GLONASS, BeiDou, and Galileo. RX45 is a multi-GNSS precision antenna and is ideal for various applications including surveys, RTK positioning and navigation, precise

guidance, and machine control. Use the RX45 antenna in challenging environments (such as near buildings and foliage) for superior multipath mitigation, stable phase center, and strong SNR's, even at low elevations. The ruggedized housing is made of an aluminum base that has been pretreated for the marine environment and will withstand salt, fog, and spray. The antenna easily passes the two-meter pole drop test.

GNSS Sensor

Signals Received: GPS L1/L2/L5, GLONASS G1/G2, BeiDou B1/B2/B3, SBAS, L-band, and Galileo E1/E5a and b

GNSS Frequency: 1.165 to 1.278 GHz
1.525 to 1.615 GHz

LNA Gain: 30 dBn

LNA Noise: 2.0 dB, typical

L-Band Sensor

L-Band

Frequency: 1.525 - 1.585 GHz operation

L-Band LNA Gain: 30 dB

Power

Input Voltage: 3.3 to 15 VDC

Input Current: 25 mA, typical

Mechanical

Enclosure:

Aluminum base with Lexan™ plastic cap

Dimensions:

4.7 H x 15.2 D (cm)

1.8 H x 6.0 D (in)

.50 kg (1.1 lbs)

Weight:

Mount:

5/8 inch female thread

RF Connector:

TNC (straight)

Environmental Storage

Temperature: -40° C to +85° C (-40°F to +185°F)

Operating

Temperature: -40° C to +70° C (-40°F to +158°F)

Enclosure Rating: IP69K

Shock/Vibration: EP455

Phase Center

Variation:

Less than 2 mm at GPS L1, for elevations above 15 degrees